


3I640A/CW


3.5" Embedded IPC Board supports Intel® Elkhart Lake ATOM® x6413E / J6412 CPU
HDMI®, DVI, LVDS, 2 x Intel 2.5 Gb Ethernet, 6 x USB, Touch Screen,
6 x COM, 2 x M.2, 1 x Mini PCIe, 1 x Mini SIM, 8DI / 8DO



Features:

- Intel® Elkhart Lake ATOM® x6413E / J6412 CPU
- 1 x DDR4 SODIMM, Max. 32GB
- Independent display: HDMI®, DVI, LVDS
- 2 x Intel 2.5 GbE LAN, 2 x USB 3.0, 4 x USB 2.0
- 6 x COM, 1 x Mini PCIe, 2 x M.2, 1 x Mini SIM
- Touch Screen, 8DI / 8DO
- TPM 2.0 (option)

Dimensions: (Unit:mm)



Specifications :

- CPU**
Intel® Elkhart Lake ATOM® x6413E / J6412 CPU
- MB Chipset**
Intel® Elkhart Lake SoC
- Graphics**
Intel® HD Graphics, Support DirectX 12.1 & OpenGL 4.5
- System Memory**
1 x DDR4 SODIMM, Max. 32GB
- Storage**
1 x M.2 B Key Type 2242 NVMe-SSD
1 x SATA
1 x M.2 SATA-SSD
- BIOS**
Insyde UEFI BIOS
- Display**
1 x HDMI®, 1 x DVI, 24 / 48bits LVDS
Touch USB interface Touch Screen controller
- TPM**
TPM 2.0 (Firmware) ; OEM Optional to Hardware TPM 2.0
- LAN**
2 x Intel 2.5 GbE I226 (external)
- Audio**
High Definition Audio Specification, Support Line-out / Mic-in / Line-in Two channel Class D Audio Amplifier
- Expansion Interface**
1 x M.2 B Key Type 2242 / 3042 (SATA / USB 2.0 / USB 3.0)
1 x M.2 B Key Type 2242 (PCIe x2 / USB 2.0), support NVMe
1 x Mini PCIe (USB 2.0 / PCIe)
1 x Mini SIM

Expansion Options

CN064	M.2 B+M key 2242 to M.2 E Key 2230, WiFi 6 + BT
CN067	M.2 B key 2242 to M.2 B Key 2252, 4G / 5G (3.7V by BOM Control)
CN059	USB to Line-out / Mic- in
CC007	USB to 4 port COM
CIO116G	SMBus to 8DI + 8DO
PW351	1 port PoE PSE
PW352	2 port PoE PSE
PW301	802.3AF / AT PD module
PW205	Wide Range power board (9~36V) with power Ignition on/off delay
PW206	12V / 24V DC to DC Redundant Power Board
PW022	Wide Range power board (24V / 48V)

- USB**
2 x USB 3.0 (external) ; 2 x USB 2.0 (external) + 2 x USB 2.0 (internal)
- Serial IO**
2 x RS232 / 422 / 485 (internal)
4 x RS232 (internal)
*COM1~COM4 pin9 5V / 12V (by Jumper) ; COM5 / 6 (OEM BOM)
- GPIO**
Hardware digital Input & Output, 8 x DI / 8 x DO
- WDT**
Hardware Watch Dog Timer, 0~255 sec programmable
- SMBus**
1 x SMBus
- PS2 KB/MS**
PS2 KB/MS (internal)
- Power Input**
DC-IN +12V or Wide Range +9~36V
- Dimension**
3.5" (146 x 102 mm) ; Weight: 150g
- Operation Temperature (100 % CPU Usage)**
-20°C~70°C (100 % CPU Usage)
-40°C by x6413E CPU
- Operation Humidity**
5~95%, non-condensing
- Chassis (OEM I/O Expansion by request)**
Box PC: TWITTER
- OS Support**
Windows® 10 IOT ; Windows® 11 IOT
Ubuntu 22.04 above, Fedora 36 above

Specification are subject to change without prior notice. ODM / OEM is available.