



TWITTER 3I640A

Fanless Embedded Computer with
Intel® Atom™ Elkhart Lake 6000 series Processor

Features:

- Intel® Elkhart Lake ATOM x6413E / Celeron J6412 Quad Core CPU
- 1 x DDR4 SODIMM, Max. 32GB
- 2 x 2.5GbE, 4 x COM, DVI, HDMI, 4 x USB
- 1 x Mini PCIe, 2 x M.2, 1 x Mini SIM
- DC-IN +12V

Specifications :

Motherboard	3I640A
CPU	Intel® Elkhart Lake ATOM x6413E Quad Core 3.0 GHz CPU Intel® Elkhart Lake Celeron J6412 Quad Core 2.6 GHz CPU
Chipset	Intel® Elkhart Lake SoC
Memory	1 x DDR4 SODIMM, Max. 32GB
Storage	M.2 SATA SSD, M.2 NVMe SSD
Expansion slots	1 x M.2 B Key Type 3042 (SATA / USB 2.0 / USB 3.0) 1 x M.2 B Key Type2242 (PCIe x2 / USB 2.0), support NVMe 1 x Mini PCIe (USB 2.0 / PCIe) 1 x Mini SIM
I/O ports	Network 2 x Intel i225 / i226 2.5 GbE USB 2 x USB 3.0 2 x USB 2.0 Serial ports 2 x RS232 / 422 / 485 2 x RS232 Display 1 x DVI, 1 x HDMI
Optional Modules & Accessory	4G / 5G, Wifi, Bluetooth, Digital I/O *SATA HDD Kit, *VESA Mount Kit *Wall mount Kit
OS Support	Windows® 11 IOT, Windows® 10 IOT Ubuntu 22.04 above, Fedora 36 above

Mechanical

Dimensions	210W x 121D x 55H mm
Weight	1.1 kg
Mounting	VESA Mount / Wall Mount*
Power	
DC input	+12V
AC input	External adapter 100 / 240V AC-DC 30W
Environment	
Operating Temp.	-20°C to +60°C (X6413E) ; -40°C by OEM Option (100 % CPU usage) 0°C to +60°C (J6412) *With wide range temperature memory & storage
Storage Temp.	-40°C to +70°C
Relative Humidity	95% @ 40°C, non-condensing
Certification	CE / FCC class A

Dimension

